



Description

The Outdoor Siren/Strobe Model SE is a battery operated, wireless combination unit designed for use in Videofied security systems.

The unit consists of a sounder, strobe light, and S²View[®] Spread Spectrum, Videofied[®], interactive, encrypted wireless circuitry for secure two-way communication with the control panel.

The siren produces an output level of 105 dB at 1 meter for three minutes, in alarm. The strobe light flashes four times per second for three minutes, in alarm.

The unit is typically installed outdoors on the structure to help responding authorities locate the alarm site. The unit should be mounted where it is protected from weather elements, at a height where intruders cannot reach to help prevent disabling the unit. A dual tamper function provides detection for both cover and mounting surface.

The unit is powered by four alkaline batteries that can last four years, depending on the amount of siren/strobe activity. The unit transmits a check-in signal every eight minutes that includes its unique identification code, along with the tamper condition and battery status.

Features

- > S²View[®] - Spread Spectrum, Videofied[®], Interactive AES Encrypted Wireless technology provides optimum signal integrity and security.
- > Sounder - provides output of 105 dB @1 meter for up to three minutes, in alarm.
- > Supervised - transmits a check-in/status signal every 8 minutes indicating tamper state and battery status.
- > Dual tamper - provides detection for both wall and cover tamper.
- > Alkaline batteries - four years.

Applications

- > Visual and audible annunciation of alarms in Videofied security systems.



Electrical Data

Power requirements	Four 1.5 V batteries
Battery type	Alkaline, D size
Battery life	Up to 4 years
RF technology	S ² View [®]
Radio type	Spread Spectrum Bidirectional
Operating frequency	920 MHz
Transmission security	AES encryption algorithm
Supervision	Polled signal every 8 minutes
Antenna	Integrated
Tamper detection	Wall and cover tampered
Speaker impedance	4 ohms
Output level	105 dB @ 1 meter
Output duration	Three minutes maximum
Flash type	Strobe light tube
Flash duration	Three minutes maximum
Flash sequence	Four flashes/sec
Operating temperature	-30°/+60°C
Maximum relative humidity	90%, non-condensing
Approvals	CE/EN50131/EN300220/INCERT/IDA/NCP (SE251) UL / FCC (SE651) A-Tick (SE751)

Physical Data

Material	ABS—ULV0
Dimensions	227 mm x 166 mm x 80 mm (LxWxD): 9 in. x 6-1/2 in. x 3 in.
Weight	880 g/31 oz. (without batteries)

Installation/Mounting

Unit/Base	Four screws secure unit to base; four screws secure unit base to mounting surface.
-----------	---

.SE means SE651 for USA/Canada, SE751 for Australia/Singapore and SE251 for Europe and rest of the world.



AUSTRALASIAN SALES - HEAD OFFICE

2A Mammoth Business Centre
7172 Bruce Hwy, Forest Glen
QUEENSLAND, Australia

Hot line : 1300 46 44 55 Or +61(0) 7 5453 73 55
Fax : +61 (0) 7 5453 73 93
www.videofied.com.au
email : support@videofied.com.au

www.videofied.com.au